Facility	10 //	E 1114	/ Name:	1 (1)		* 4 11	
- a ∩ IIIt\	/ ##	Facilit\	/ Name:	Location:	P	ermit #:	
ı avılır		I acilit	/ Name.	Location.		$CIIIIIII \pi$.	



Pipe Installation Supplement B

Your application is not complete until **all** requested information is submitted. Please complete every item on this supplement to avoid delays in processing your request.

Permit fees Environmental Asses	oplication for Undergroussment Questionnaire (Design Report (if requi	ired)	ajor Installation	NLY
Tag Number (if applicable)				
Tank Capacity (gallons)				
Substance Stored				
Product Pipe Material	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other
Product Pipe Construction	☐ Double-walled ☐ Single-walled ☐ Other	☐ Double-walled ☐ Single-walled ☐ Other	☐ Double-walled ☐ Single-walled ☐ Other	☐ Double-walled ☐ Single-walled ☐ Other
Pipe Manufacturer				
Type of Pipe	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction	☐ Gravity ☐ Pressurized ☐ Safe Suction ☐ U.S. Suction
Leak Detection	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other	Interstitial Monitoring Continuous Manual Safe Suction (self-testing) Tightness Test Leak Detector GW Monitoring Vapor Monitoring Other
Corrosion Protection	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible	☐ Galvanic ☐ Impressed Current ☐ Non-corrodible
Vent Pipe Material	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other	☐ Flexible ☐ FRP ☐ Steel with CP ☐ Other

_	Checklist for proposed installation:	
	Depth to groundwater	
	Make and model of all pressurized line leak detection equipment (for ELLD include series)	
	☐ MLLD ☐ ELLD ☐ LD panel	
	How is the LD panel programmed? (indicate all)	
	□ 0.1 gph annual test □ 0.2 gph monthly test □ 3 gph continuous	; test
_	☐ Sound a continuous alarm ☐ De-energize the turbine ☐ Autodialer	
님	Make and model of all interstitial piping equipment	
	Length of pipe run protected by line leak detector for each tank system	
	How do the liquid sensors stop the flow of fuel in the event of a leak?	
Ш		
	☐ Sound a continuous alarm☐ Close a solenoid at the tank top☐ De-energize the turbine☐ Autodialer	
	Corrosion protection method for each metal component that will be in contact with the ground	
_	· · · · · · · · · · · · · · · · · · ·	
	Make and model of any other equipment to be installed	
Ш	wake and model of any other equipment to be installed	
닏	Length of each new vent piping run	
Ш	For connections to existing pipe, also describe:	
	Type of existing product pipes and method of connection	
	Total length of each new product piping run	
	☐ Make/model of existing line leak detection equipment to be replaced	
	Describe the project—what are you planning to do? (attach additional sheets if necessary). Ir	clude any special
	design issues and any information not included above.	
Site PI	an to include the following elements at a minimum:	
□F	acility name	ow
N	ajor site features Direction of ground slope	
	djacent water wells, public sewers, streams or bodies of water within 100 feet of installation	
	imensioned or scaled distances between property lines, buildings, tanks and proposed pipe(s)	
	ch existing UST system, locate and label the following elements by dimension or scaled location	on:
	anks (AST and UST) Product Pipe(s)* Dispenser(s)	
	ump(s)*	
	w only if any existing UST component requires disassembly or relocation	
	ch proposed UST system pipe install locate the following elements by dimension or scaled in p	
	roduct pipe(s)	
	eak detection monitoring equipment** Line leak detector if not installed in STP has been been been been been been been bee	lousing
	ex connectors and method of corrosion protection**	
	connecting to existing pipe made by a different manufacturer, show connection location and de	etailed cross-section
	or double-walled and/or suction pipe runs, show flow direction through the system and location	
	talling a suction system, also include:	
	☐ Check valves** ☐ Solenoid valves** ☐ Product pipe cross-sections indicating dir	ection and slope**
**Sho	w relative location only (do not dimension or scale)	
Enviro	nmental Assessment:	Yes No
1. Is th	e depth to groundwater less than 50 feet below ground surface?	Yes No
 Is th Is th 	e depth to groundwater less than 50 feet below ground surface? e distance to surface water less than 100 feet from the project boundary?	Yes No
 Is th Is th Is a 	e depth to groundwater less than 50 feet below ground surface?	Yes No

If you answered yes to **any** of these questions, you must submit an Environmental Assessment Questionnaire with your permit application.